



Fireplace Inserts • Patioflame • Gas Fireplaces • Charcoal Grills • Wood Stoves
Heating & Cooling • Electric Fireplaces • Outdoor Fireplaces • Gas Grills

SPECIFICATIONS

COMPARISON CHART

| Series | Efficiency (AFUE) | Single Stage | Two-Stage | SureView Window | PSC Motor | DC X-13 Motor (NPX Models) | ECM EnerSave EON Motor | Primary Stainless Steel Heat Exchanger | Secondary Stainless Steel Heat Exchanger | LED Cabinet Lights | Built-in UV Light Air Purifier | Four-Sided Insulated Cabinet | Made In Canada |
|--------|-------------------|--------------|-----------|-----------------|-----------|----------------------------|------------------------|--|--|--------------------|--------------------------------|------------------------------|----------------|
| 9700 | 97% | | • | • | | | • | • | • | • | • | • | |
| 9600 | 96% | | • | • | | | • | | • | | | • | |
| 9500 | 95% | • | | | | • | | | • | | | • | |
| 9200 | 92.10% | • | | | • | | | | • | | | • | |

| HEATING CAPACITIES | NPX030S2B | NPX040S2B | NPX060S3B | NPX080S3B | NPX080S4B | NPX100S5B | NPX120S5B |
|-----------------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Efficiency (AFUE) | 95% | 95% | 95% | 95% | 95% | 95% | 95% |
| Input BTU/hr 0-4500' | 30,000 | 40,000 | 60,000 | 80,000 | 80,000 | 100,000 | 120,000 |
| Output BTU/hr 0-4500' | 28,500 | 38,000 | 57,000 | 76,000 | 76,000 | 95,000 | 114,000 |
| CABINET DIMENSIONS (INCHES) | NPX030S2B | NPX040S2B | NPX060S3B | NPX080S3B | NPX080S4B | NPX100S5B | NPX120S5B |
| Width (in) | 17 1/2 | 17 1/2 | 17 1/2 | 17 1/2 | 22 1/2 | 22 1/2 | 22 1/2 |
| Depth (in) | 29 1/2 | 29 1/2 | 29 1/2 | 29 1/2 | 29 1/2 | 29 1/2 | 29 1/2 |
| Height (in) | 32 7/8 | 32 7/8 | 32 7/8 | 32 7/8 | 32 7/8 | 32 7/8 | 32 7/8 |
| CLEARANCES AND VENTING | NPX030S2B | NPX040S2B | NPX060S3B | NPX080S3B | NPX080S4B | NPX100S5B | NPX120S5B |
| Clearances to Combustibles | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Minimum Vent Size (in) | 1 1/2 | 1 1/2 | 1 1/2 | 2 | 2 | 2 | 3 |
| Maximum Vent Size (in) | 2 | 2 | 3 | 3 | 3 | 3 | 3 |
| Minimum Vent Length (ft) | 15 | 15 | 15 | 15 | 15 | 15 | 15 |
| Maximum Vent Length (ft) | 75 | 75 | 100 | 100 | 100 | 100 | 100 |
| AIRFLOW AND COOLING | NPX030S2B | NPX040S2B | NPX060S3B | NPX080S3B | NPX080S4B | NPX100S5B | NPX120S5B |
| Motor Type and Size X-13 | 1/3 hp | 1/3 hp | 1/2 hp | 1/2 hp | 3/4 hp | 3/4 hp | 1 hp |
| AC Tonnages | 1½, 2, 2½ | 1½, 2, 2½ | 2, 2½, 3 | 2, 2½, 3 | 2, 3, 4 | 3, 4, 5 | 3, 4, 5 |

*See table 4 in manual for all venting configurations



24 Napoleon Road, Barrie, Ontario, Canada L4M 0G8
103 Miller Drive, Crittenden, Kentucky, USA 41030
7200 Trans Canada Highway, Montreal, Quebec, Canada H4T 1A3

Tel: 705-721-1212 Fax: 705-722-6031
napoleonheatingandcooling.com



Authorized Dealer

Canada

ENERGUIDE

Annual Fuel Utilization Efficiency (AFUE)
Gas- or Propane-fired forced-air furnace
with a high efficiency motor

THIS MODEL
95.0

90%98%

All specifications and designs can change without notice to allow for on-going product improvement. Images may not be exactly as shown. Consult your owners manual for current information. Check all local and national building codes and gas regulations. Napoleon® is a registered trademark of Wolf Steel Ltd. © Wolf Steel Ltd.